



4-Ice and water guard by others
 17-rafter
 22-thermal insulation
 100-FVS solar powered venting Skylight FAKRO
 147-top part of the flashing EL FAKRO
 148-EL FAKRO flashing side element
 149-EL FAKRO flashing lower element

SOLAR POWERED VENTING SKYLIGHT FVS

Window size[in] SxL	S [in]	S [mm]	L [in]	L [mm]	Rough opening			
					W [in]	W [mm]	R [in]	R [mm]
24x27	24 1/2	623	27 1/2	699	22 1/2	568	26 1/2	678
24x38	24 1/2	623	38 1/2	978	22 1/2	568	37 1/2	957
24x46	24 1/2	623	46 3/8	1178	22 1/2	568	45 1/2	1157
24x55	24 1/2	623	55	1397	22 1/2	568	54	1376
24x70	24 1/2	623	70 3/4	1797	22 1/2	568	70	1776
32x38	32 1/2	826	38 1/2	978	30 1/2	771	37 1/2	957
32x46	32 1/2	826	46 3/8	1178	30 1/2	771	45 1/2	1157
32x55	32 1/2	826	55	1397	30 1/2	771	54	1376
48x27	48 1/2	1232	27 1/2	699	46 1/2	1177	26 1/2	678
48x46	48 1/2	1232	46 1/2	1178	46 1/2	1177	45 1/2	1157

	FVS Skylight	EL	SLATE	15° - 85°

Vertical and horizontal cross-sections: FVS opening Skylight with flashing EL for flat tiled roofs	FORMAT A4	SCALE 1:10/1:5	DATE 6.2020
--	--------------	-------------------	----------------

Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality on the roof. This drawing is FAKRO's property and cannot be published, or used publicly without our written consent.