


- 79 - Fire-rated hatch
- 80 - Tread
- 86 - Hinge
- 88 - Side bracket
- 90 - LXH handrail
- 93 - LXS stile end
- 94 - Stringer (ladder side element)
- 714 - Fire-resistant sealant
- 715 - Insulation: rock wool with a min. density of 2.5lb/ft³
- 716 - Spacing washer
- 765 - Plastic trims LXL-PVC (US)

Step length	E	13 1/4"
Step width	S	3 1/8"
Step thickness	Z	7/8"

LWF II		22 1/2" x 47"	25" x 47"	22 1/2" x 54"	25" x 54"	30" x 54"
Ceiling height	H	7'5" - 8'11"		7'11 1/2" - 10'1"		
Rough opening	A x B	22 1/2" x 47"	25" x 47"	22 1/2" x 54"	25" x 54"	30" x 54"
Outside frame dimensions	W x L	22" x 46 5/8"	24 1/2" x 46 5/8"	22" x 53 1/2"	24 1/2" x 53 1/2"	29 1/2" x 53 1/2"
Internal dimensions	M x N	20 1/2" x 44 7/8"	23" x 44 7/8"	20 1/2" x 51 1/4"	23" x 51 1/4"	28" x 51 1/4"
Projection	R	67"		73 1/4"		
Landing space	C	59"		65 1/4"		
Folded ladder height	K	15"				
Board movement after opening	P	1"				
Distance between steps	G	9 7/8"		10 1/2"		
Frame height		8 5/8"				
Approx. Weight (kg)		103	107	111	115	126



Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.

Technical drawing: The LWF Loft Ladder	FORMAT:	SCALE:	DATE:
	A4	1:20/1:10	04.2016