



- 440-Finishing lining
- 714-Fire-resistant sealant
- 715-Insulation: rock wool with a min.density of  $\rho=60\text{kg/m}^3$
- 732-DWF60 Fire-resistant L-shaped combination door FAKRO

DWK	DWF KNEE WALL ACCESS DOOR DOOR										
	Rough opening				Frame external dimensions		Frame Internal dimensions		Jamb Size		Frame thickness
	A	B	A	B	W	L	M	N	S	Z	
	[in]	[in]	[cm]	[cm]	[in]	[in]	[in]	[in]	[in]	[in]	
21x31	21½"	31½"	55	80	21"	31"	19"	28½"			
27x35	27½"	35½"	70	90	27"	34½"	24½"	32½"	3½"	1"	
27x43	27½"	43½"	70	110	27"	42½"	24½"	40½"			



Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.

Vertical and horizontal cross-section: DWF60 L-Shaped Combination Doors	FORMAT: LETTER	SCALE: 1:15	DATE: 10.2024
--	-------------------	----------------	------------------