

## DWF 60\_L8B

SCH / DW / DWF



The FAKRO DWF60 fire-rated knee wall door provides safe access to non-livable spaces with E11/EI2 60 fire resistance. It features a removable handle that can stay in the door or be removed after use. The door is equipped with three seals: a perimeter gasket, a compression seal for airtight closure, and an intumescent seal that expands during fire to block air and smoke. The construction includes a pinewood frame, mineral wool insulation (3 1/8"), and a white HDF panel, ensuring durability and energy efficiency. Fully assembled, it supports universal left or right swing installation.

### Functionality

<b>Installation method</b>	<ul style="list-style-type: none"> <li>completely assembled;</li> <li>universal fit, left or right swing;</li> </ul>
<b>Fire-resistance [minutes]</b>	E11/EI2 60
<b>Fire resistance</b>	Yes
<b>Thermal insulation [R-value]</b>	12
<b>Equipment</b>	<ul style="list-style-type: none"> <li>trim;</li> <li>handle;</li> <li>expanding seal;</li> </ul>
<b>Insulation</b>	Yes
<b>Tightness class</b>	4th highest class

### Frame (dimensions)

<b>Frame material</b>	pinewood
<b>Frame depth [inch]</b>	3 9/16"
<b>Frame element thickness [inch]</b>	1 1/16"
<b>Number of seals [pcs.]</b>	2

### Door sash

<b>Door type</b>	Fire-resistant
<b>Door color</b>	White
<b>Thermal insulation thickness (US) [inch]</b>	3 1/8"
<b>Sash thickness (US) inch</b>	3 3/8"

### Frame size

SKU	Size	L - Outside frame dimension - height [inch]	W - Outside frame dimension - width [inch]	Inside frame dimension - height [inch]	Inside frame dimension - width [inch]
869485	21"x31"	31	21	29	19
869486	27"x35"	35	27	33	25
869487	27"x43"	43	27	41	25

