



- 78-Spring
- 80-Tread
- 84-Thermo-insulated hatch
- 86-Hinge
- 88-Side bracket
- 90-LXH handrail
- 94-Stringer (ladder side element)
- 686-Lining slats LXL-PVC FAKRO
- 688-Plastic fastener (the so-called "click")

P	S	Z	G
Board movement after opening	Tread width	Tread thickness	Distance between treads
[in]	[in]	[in]	[in]
2 1/8"	3 1/8"	5/8"	9 1/8"

Loft ladder dimensions									
H	A	B	K	R	C	E	T	WxL	MxN
Room height	Width ceiling opening dimensions	Length ceiling opening dimensions	Folded ladder height	Swing space	Distance after ladder unfolding	Tread length	Box height	Box external dimensions	Internal box dimensions
[in]	[in]	[in]	[in]	[in]	[in]	[in]	[in]	[in]	[in]
7'5"-8'11"	22 1/4"	47"	12 1/2"	64 1/2"	58"	13 1/4"	8 5/8"	22"/46 3/8"	20 1/2"/44 1/2"
	25"	47"						24 1/2"/46 3/8"	23"/44 1/2"
7'10"-10'11"	22 1/2"	54"	12 1/2"	72"	65"	13 1/4"	8 5/8"	22"/53 1/2"	20 1/2"/51 3/4"
	25"	54"						24 1/2"/53 1/2"	23"/51 3/4"
	30"	54"						29 1/2"/53 1/2"	28"/51 3/4"

FAKRO



Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.

Technical drawing:
The LWT 3-section Loft Ladder

FORMAT:
A4

SCALE:
1:20/1:10

DATE:
05.2015