TECHNICAL SPECIFICATION

ATTIC LADDER LML

I. APPLICATION

Folding attic ladders enable safe and easy access to non-inhabited spaces without the need for installing costly and space consuming staircases. Insulated metal model - LML for garages, inside houses, projects with insulation requirements.

II. STRUCTURE

No.	Element	Description		
1	Hatch	insulated, sandwich type, white thickness: 1¾". thermal insulation thickness: 1¼". No lock — unloading mechanism automatically presses the hatch to the box, opening with the use of a control rod		
2	Frame	pinewood ladder box includes a steel frame, finishing linings slats and a quick installation syste height: 12¾″ seal: 1 pcs		
3	Ladder	metal ladder width: 151⁄8" distance between steps: 93⁄4".		
4	Steps	metal, equipped with anti–slip profile. steps width: 51%" length: 1334"		
5	Standard Accessories	retractable stile ends red handrail with ladder unfolding mechanism control rod for opening the hatch white metal trim installation brackets		

III. DIMENSIONS

No.	Ladder Size	Room height		
1	23,5″x 47″	9'2 ¾ ″		
2	27,5″x 51″	10″		

IV. TECHNICAL PARAMETERS Maximum loading 350 lbs Heat transfer coefficient R-value: 5.2

V. COMPATIBLE ACCESSORIES					
Ladder Balustrade LXB-U	The balustrade is available in one standard size 30"x54" for all attic ladders.				
Box extension LXN	The standard box height is 4". While ordering the LXN please provide ladder type and size.				
Upper hatch LXW	The height of the upper hatch box is 7¾".				






VI. ASSEMBLY INFORMATION

The **LML** Attic Ladder is delivered to the customer fully assembled and does not require any pre-installation work. Installation of the product must be carried out in accordance with the included fitting instructions.

Pre-installation, installation and safety instruction: http://www.fakrousa.com/our-products/offer/-installation-instructions/ Installation movies: http://www.fakrousa.com/our-products/offer/attic-ladders/

VII.DETAILED DIMENSIONS



LML		23½ x 47	27½ x 51
Ceiling height	Н	7'7¾" - 9' 2¾"	8'4¾" - 10"
Rough opening		23½″ x 47″	27½″ x 51″
Outside frame dimensions		23″x 46¾″	27″ x 50%″
Outside frame dimensions including trim		25½" x 48¼"	28½″x 52¼″
Internal dimensions		215⁄8″ x 447⁄8″	25¼″ x 48%″
Projection		65″	69½″
Landing space		471⁄4″	51¼″
Folded ladder height		12½″	12½″
Frame height		12½″	12½″